

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A visual system, comprising:

a CCD or CMOS matrix having a sensitive area, and

a plurality of optical devices with different directions and/or fields of view and/or modes of optical separation,

wherein said sensitive area of the matrix is divided into a plurality of separated sub-areas

designed for different specific functions, part of said ~~sub-areas~~ plurality of separated sub-areas being dedicated to scene monitoring and part of ~~the said plurality of separated~~ sub-areas being dedicated to detection of environmental parameters, said division being achieved by said plurality of optical devices.

2. (currently amended): The visual system according to claim 1, wherein the system is installed in a motor vehicle on a front portion of an inner rear-view mirror of the motor vehicle and performs one or more functions among: rain detection, windscreen misting detection, fog detection, dusk detection, tunnel detection, vehicle meeting detection, and monitoring of a scene in front of the vehicle.

3. (currently amended): The visual system according to claim 1, wherein the matrix is a linear or logarithmic, monochromatic (or color) VGA CMOS matrix.

4. (currently amended): The visual system according to claim 1, wherein at least one of the sub-areas is designed for front monitoring.

5. (currently amended): The visual system according to claim 4, wherein the sensitive area of the matrix also has a specific sub-area for rain and misting detection.

6. (original): The visual system according to claim 5, wherein the sensitive area of the matrix further comprises an additional specific sub-area for vehicle meeting detection.

7. (currently amended): The visual system according to claim 6, wherein the sub-area dedicated to rain detection functions with an emitter.

8. (currently amended): The visual system according to claim 7, wherein said area dedicated to rain function is also dedicated to wind-screen misting function.

9. (currently amended): The visual system according to claim 8, wherein dusk function is performed by a specific sub-area of a CMOS matrix.

10. (currently amended): The visual system according to claim 9, wherein tunnel function is performed by using part of the area dedicated to front monitoring function.

11. (currently amended): The visual system according to claim 10, wherein fog function is performed both with a dedicated sub-area, with an active technique for local fog detection, and with passive technique for fog bank detection in another sub-area corresponding to the one dedicated to front monitoring or contained therein.

12. (currently amended): The visual system according to claim 11, wherein vehicle meeting function is performed by using two dedicated sub-areas or a sub-area dedicated to front monitoring, in a color matrix or in a monochromatic matrix by means of optical filter laid with a discretization degree at pixel level, though only in the area or sub-area of the matrix dedicated to front monitoring.

13. (currently amended): The visual system according to claim 1, wherein the matrix sensor has a protection window made of glass or transparent plastic, also acting as support for one or more optical fibers and a prism carrying to selected sub-areas of the matrix an optical signal picked up by the ~~latter~~prism.

14. (currently amended): The visual system according to claim 13, wherein said optical fibers have proximal ends fitted into holes made into said protection window.

15. (currently amended): The visual system according to claim 13, further comprising means for optical insulation between the sub-area dedicated to front monitoring and ~~the said~~ plurality of separated sub-areas dedicated to rain, misting, fog and dusk functions, the means for

optical insulation partially covering of a surface of a matrix protection window, on the side towards the matrix, with a layer of absorbing or reflecting material.

16. (currently amended): The visual system according to claim 13, further comprising means for optical insulation of the sub-area dedicated to rain function from the influence of other functions, said means for optical insulation including partial covering prism faces with a layer of absorbing or reflecting material, and a hole made into the optical window, in which the hole inner walls are covered.

17. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to rain function receives the optical signal from an optical system comprising, in series, a prism with optical insulation, a filter and an objective with optical axis orthogonal to windscreen.

18. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to windscreen misting function receives the optical signal from an optical system comprising a prism with optical insulation, a filter and an objective with optical axis orthogonal to wind-screen.

19. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to dusk function receives the optical signal through an optical fiber.

20. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to tunnel function receives the optical signal through an objective dedicated also to front monitoring function.

21. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to fog function, based on active technique, receives the optical signal through an optical system comprising a ball or grin lens or even no lens at all together with an end of an optical fiber, possibly with another grin or micro-optical lens or even with no lens at all on the other end of the optical fiber, together with a high-pass/interferential filter, and a collection lens.

22. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to fog function, based on passive technique, receives the optical signal through an objective dedicated also to front monitoring function.

23. (currently amended): The visual system according to claim 13, wherein two sub-areas dedicated to vehicle meeting function receive the optical signal through filters together with an objective.

24. (currently amended): The visual system according to claim 13, wherein in the variant of vehicle meeting function based on the use of a sub-area dedicated to front monitoring in a color matrix or in a monochromatic matrix, the optical signal is collected by means of a same objective, which is dedicated to front monitoring function.

25. (currently amended): The visual system according to claim 13, wherein a sub-area dedicated to front monitoring function receives the optical signal through an objective with optical axis shifted with respect to matrix center.

26. (currently amended): The visual system according to claim 1, wherein some sub-areas are reserved for unused pixels necessary as additional separation between used sub-areas.